
Power Optimiser

For Australia

S440 / S500 / S500B



POWER OPTIMISER

PV power optimisation at the module level

- / Specifically designed to work with SolarEdge inverters
- / Detects abnormal PV connector behavior, preventing potential safety issues*
- / Module-level voltage shutdown for installer and firefighter safety
- / Superior efficiency (99.5%)
- / Mitigates all types of modules mismatch- loss, from manufacturing tolerance to partial shading
- / Flexible system design and compatible with bifacial PV modules for maximum space utilisation
- / Faster installations with simplified cable management and easy assembly using a single bolt
- / Next generation maintenance with module safety

* Functionality subject to inverter model and firmware version

/ Power Optimiser

For Australia

S440 / S500 / S500B

	S440	S500	S500B	Units
INPUT				
Rated Input DC Power ⁽¹⁾	440	500		W
Absolute Maximum Input Voltage (Voc)	60	125		Vdc
MPPT Operating Range	8 – 60	12.5 – 105		Vdc
Maximum Short Circuit Current (Isc) of connected PV Panel	14.5	15		Adc
Maximum Efficiency		99.5		%
Weighted Efficiency		98.8		%
Overvoltage Category		II		
Input Overcurrent Protection		15		Adc
OUTPUT DURING OPERATION				
Maximum Output Current		15		Adc
Maximum Output Voltage	60	80		Vdc
OUTPUT DURING STANDBY (POWER OPTIMISER DISCONNECTED FROM INVERTER OR INVERTER OFF)				
Safety Output Voltage per Power Optimiser		1 ± 0.1		Vdc
STANDARD COMPLIANCE				
EMC	FCC Part 15 Class B, IEC61000-6-2, IEC61000-6-3			
Safety	IEC62109-1 (class II safety), UL1741			
Material	UL94 V-0, UV Resistant			
RoHS	Yes			
Fire Safety	VDE-AR-E 2100-712:2018-12			
INSTALLATION SPECIFICATIONS				
Maximum Allowed System Voltage	1000			Vdc
Dimensions (W x L x H)	129 x 155 x 30	129 x 165 x 45		mm
Weight	720	790		gr
Input Connector	MC4 ⁽²⁾			
Input Wire Length	0.1 / 0.9 ⁽³⁾			m
Output Connector	MC4			
Output Wire Length	(+) 2.3, (-) 0.10			m
Operating Temperature Range ⁽⁴⁾	-40 to +85			°C
Protection Rating	IP68 / NEMA6P			
Relative Humidity	0 – 100			%

(1) Rated power of the module at STC will not exceed the Power Optimiser Rated Input DC Power. Modules with up to +5% power tolerance are allowed.

(2) For other connector types please contact SolarEdge. Please note that with other connector types, the wire length will be 0.16m. The Sense Connect feature will not detect thermal events on these connectors.

(3) The Sense Connect feature will not detect thermal events on input connectors when the input wire length is 0.9m.

(4) Power de-rating is applied for ambient temperatures above +85°C for S440 and S500, and for ambient temperatures above +75°C for S500B. Refer to [Power Optimisers Temperature De-Rating Technical Note](#) for more details.

PV System Design Using a SolarEdge Inverter	SolarEdge Home Genesis / SolarEdge Home Hub	Three Phase Residential	Three Phase Commercial	Units
Minimum String Length (Power Optimisers)	S440, S500 S500B	8 6	9 8	16 14
Maximum String Length	25		50	
Maximum Nominal Power per String ⁽⁵⁾	5700 (6000 with SE8250H / SE10000H)	5625	11250 ⁽⁶⁾	W

(5) If the inverter's rated AC power ≤ maximum nominal power per string, then the maximum power per string will be able to reach up to the inverter's maximum input DC power. Refer to the [Single String Design Guidelines Application Note](#) for more details.

(6) When using more than a single string, it is allowed to install up to 13500W per string when the maximum power difference between each string is up to 2000W.

(7) It is not allowed to mix S-series and P-series Power Optimisers in new installations.

