

# **MAXEON 3** SOLAR PANEL

390-400 W | Up to 22.6% Efficient





#### **More Lifetime Energy**

Designed to maximise energy generation through leading efficiency, enhanced performance in high temperatures, and higher energy conversion in low-light conditions like mornings, evenings and cloudy days.

### **Uncompromising Durability**

Engineered to power through all types of weather conditions—from crack-resistant cells and reinforced connections that protect against fatigue and corrosion, to an electrical architecture that mitigates the impact of shade and prevents hot-spot formation.



# **Superior Sustainability**

Clean ingredients, responsible manufacturing, and lasting energy production for 40 years make SunPower Maxeon panels the most sustainable choice in solar.



## The Industry's Longest Warranty

SunPower Maxeon panels are covered by a 40-year warranty<sup>1</sup> backed by extensive third-party testing and field data from more than 33 million panels deployed worldwide.

Product and power coverage 40 Years
Year 1 minimum warranted output 98.0%
Maximum annual degradation 0.25%




#### MAXEON 3 POWER: 390-400 W | EFFICIENCY: Up to 22.6%

| Electrical Data                     |              |               |              |  |
|-------------------------------------|--------------|---------------|--------------|--|
|                                     | SPR-MAX3-400 | SPR-MAX3-395  | SPR-MAX3-390 |  |
| Nominal Power (Pnom) <sup>2</sup>   | 400 W        | 395 W         | 390 W        |  |
| Power Tolerance                     | +5/0%        | +5/0%         | +5/0%        |  |
| Panel Efficiency                    | 22.6%        | 22.3%         | 22.1%        |  |
| Rated Voltage (Vmpp)                | 65.8 V       | 65.1 V        | 64.5 V       |  |
| Rated Current (Impp)                | 6.08 A       | 6.07 A        | 6.05 A       |  |
| Open-Circuit Voltage (Voc) (+/-3%)  | 75.6 V       | 75.4 V        | 75.3 V       |  |
| Short-Circuit Current (Isc) (+/-3%) | 6.58 A       | 6.56 A        | 6.55 A       |  |
| Max. System Voltage                 |              | 1000 V IEC    |              |  |
| Maximum Series Fuse                 |              | 20 A          |              |  |
| Power Temp Coef.                    |              | −0.27% / °C   |              |  |
| Voltage Temp Coef.                  |              | −0.236% / ° C |              |  |
| Current Temp Coef.                  |              | 0.058% / ° C  |              |  |

| Operating Condition And Mechanical Data |  |  |
|---|--|--|
| Temperature                             | -40°C to +85°C                               |  |
| Impact Resistance                       | 25 mm diameter hail at 23 m/s                |  |
| Solar Cells                             | 104 Maxeon 3 Cells                           |  |
| Tempered Glass                          | High-transmission tempered anti-reflective   |  |
| Junction Box                            | IP-68, Stäubli (MC4), 3 bypass diodes        |  |
| Weight                                  | 19 kg  |  |
| Max. Load <sup>6</sup>                  | Wind: 2400 Pa, 244 kg/m² front & back        |  |
|   | Snow: 5400 Pa, 550 kg/m² front               |  |
| Frame                                   | Class 1 black anodized (highest AAMA rating) |  |

| Tests And Certifications                     |  |  |
|--|--|--|
| Standard Tests <sup>3</sup>                  | IEC 61215, IEC 61730   |  |
| Quality Management Certs                     | ISO 9001:2015, ISO 14001:2015  |  |
| Ammonia Test                                 | IEC 62716  |  |
| Desert Test                                  | IEC 60068-2-68, MIL-STD-810G   |  |
| Salt Spray Test                              | IEC 61701 (maximum severity)   |  |
| PID Test                                     | 1000 V: IEC 62804  |  |
| Available Listings                           | TUV  |  |
| IFLI Declare Label                           | First solar panel labeled for ingredient transparency and LBC-compliance. <sup>4</sup>   |  |
| Cradle to Cradle Certified™<br>Bronze        | First solar panel line certified for material health, water<br>stewardship, material reutilisation, renewable energy &<br>carbon management, and social fairness. <sup>5</sup> |  |
| Green Building Certification<br>Contribution | Panels can contribute additional points toward LEED and BREEAM certifications.   |  |
| EHS Compliance                               | RoHS, OHSAS 18001:2007, lead free, REACH SVHC-163  |  |











Please read the safety and installation instructions. Visit www.sunpower.maxeon.com/int/PVInstallGuideIEC Paper version can be requested through techsupport.ROW@maxeon.com

- 1 40-year warranty is not available in all countries or all installations and requires registration, otherwise our 25-year warranty applies. Service availability varies by country and installation provider.
- 2 Standard Test Conditions (1000 W/m² irradiance, AM 1.5, 25° C). NREL calibration Standard: SOMS current, LACCS FF and Voltage.
- 3 Class C fire rating per IEC 61730.
- 4 Maxeon DC panels first received the International Living Future Institute Declare Label in 2016.
- 5 Maxeon DC panels are Cradle to Cradle Certified™ Bronze -

www.c2ccertified.org/products/scorecard/e-series\_xseries\_solar\_panels\_-\_sunpower\_corporation. Cradle to Cradle Certified $^{\text{TM}}$  is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.

6 Safety factor 1.5 included.

Made in Philippines (Cells)
Assembled in Mexico (Module)

Specifications included in this datasheet are subject to change without notice.

©2022 Maxeon Solar Technologies. All Rights Reserved.

View warranty, patent and trademark information at maxeon.com/legal.



MAKER OF SUNPOWER PANELS